



**Builders' Solutions** 

**SDS** GHS Safety Data Sheet PROFILE Products, LLC

Flexterra® High Performance-Flexible Growth Medium™(HP-FGM™)

MSDS Number: CON062

Revision Date: 1/1/14 Page 1 **of** 5

#### **PRODUCT AND COMPANY IDENTIFICATION**

#### Manufacturer & Marketed Under

System Builders Maintenance Services Sdn. Bhd. No. 17, Jalan Metro Perdana Barat 8, Sri Edaran Light Industrial, 52100 Kuala Lumpur, MY.

Phone:	(603) 6250 9892
Fax:	(603) 6250 9885
Email:	info@systembuilders.com.my
Web:	www.systembuilders.com.my
	,

Product Name:	Flexterra® High Performance-Flexible Growth Medium™(HP-FGM™)
Revision Date:	1/1/14
MSDS Number:	CON062
CAS Number:	Not applicable
Product Use:	Erosion control and revegetation mulch for hydraulic seeding.

Product Description: Green dyed wood fibers, man-made biodegradable fibers, minerals and a proprietary binder mixture.

2	HAZARDS IDENTIFICATION
Route of Entry:	Inhalation, skin contact, eye contact
Inhalation:	Wood may cause sneezing, irritation, and dryness of the nose and throat. Dust may aggravate pre-existing respiratory conditions.
Skin Contact:	Wood dust can cause irritation. Skin absorption is not known to occur.
Eye Contact:	Wood dust can irritate the eyes.
Ingestion:	No reports of human ingestion.
NFPA:	Health = 1, Fire = 1, Reactivity = $0$



Health = 1, Fire = 1, Reactivity = 0





MSDS Number: CON062

Flexterra® High Performance-Flexible Growth Medium™(HP-FGM™)

Revision Date: 1/1/14 Page 2 of 5

OSHA Classification: Wood dust is a hazardous substance as defined by the Hazard Communication Standard 29CFR 1910.1200

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas # Perc. Chemical Name

N/A | Proprietary | Hydrocolloidal Based Polysaccharide Tackifier

9000300 | Proprietary | Guar Gum

 4
 FIRST AID MEASURES

 Inhalation:
 Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation persists. In high dust levels wear dust mask.

 Skin Contact:
 Usually not a problem. Wash off with running water if irritation is experienced.

 Eye Contact:
 Open eyelids and flush with water.

 Ingestion:
 Get medical attention.

FIRE FIGHTING MEASURES

Flammability:Combustible productFlash Point:Not applicableFlash Point Method:Not applicableAutoignition Temp:200-260°C (400-500°F)

Conditions to avoid: In contact with flames or hot surfaces.

Flammable- Extinguish with water; same as a wood fire

ACCIDENTAL RELEASE MEASURES

Scoop up product. Wear goggles and respirator if dust is produced in unventilated areas. Wet product will be slippery.





Flexterra® High Performance-Flexible Growth Medium™(HP-FGM™)

MSDS Number: CON062

Revision Date: 1/1/14 Page 3 of 5

7	HANDLING AND STORAGE
Handling Precautions:	Clean up areas where dust settles. Minimize blowdown or other practices that generate high airborne dust concentrations.
Storage Requirements	Store in a cool, dry place. Keep away from sources of ignition.

8	8 EXPOSURE CONTROLS/PERSONAL PROTECTION	
Engineering Controls:	None required for outdoor mixing and application. Use dust collection system for indoor handling operations.	
Personal Protective Eq	<ul> <li>Leather, plastic or rubber gloves could be worn to minimize skin irritation.</li> <li>Respirators: When handling methods generate dust at concentrations that exceed occupational exposure limits, wear a NIOSH approved respirator. A fabric respirator or a facepiece respirator with dust cartridges will generally provide adequate protection.</li> <li>Footwear: The product is slippery when wet. Wear appropriate footwear.</li> </ul>	

9	PHYSICAL AND CHEM	ICAL PROPERTIES	
Appearance: Physical State:	Dyed green wood fibers - Pine & mixed hardwoods Wood Fibers <b>Odor:</b> Mild wood odor		
Spec Grav./Density: Vapor Pressure:	Lighter than water N/A		

### STABILITY AND REACTIVITY

Stability:	Stable product.
Conditions to Avoid:	Contact with strong acids and oxidizers may generate heat. Product may ignite at temperatures in excess of 200°C (400°F).
Materials to Avoid:	Strong acids and oxidizers.
Hazardous Polymerization:	Will not occur.





Flexterra® High Performance-Flexible Growth Medium™(HP-FGM™)

MSDS Number: CON062

Revision Date: 1/1/14

Page 4 of 5

### **TOXICOLOGICAL INFORMATION**

EFFECTS OF CHRONIC EXPOSURE:

Inhalation: Frequent and repeated exposure to wood dust is associated with an increased risk of developing nasal cancer. Skin Contact: Although rare, wood dust may cause dermatitis in sensitized people.

Occupational Exposure Limits:

Wood dusts- All other species: ACGIH (2007): TLV-TWA 1 mg/m<sup>3</sup> (Inhalable fraction); A4 Particulates Not Otherwise Regulated (PNOR): OSHA: PEL-TWA 15 mg/m<sup>3</sup> (Total Dust); 5 mg/m<sup>3</sup> (Respirable fraction)

Irritancy: Wood dust is a mild irritant

Sensitization: Some wood dusts may cause allergic skin reactions

ECOLOGICAL INFORMATION

Guar Gum (CAS# 9000-30-0) is listed as an inert ingredient permitted for use in nonfood use pesticide products by EPA. It is also classified under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA) as a minimal risk inert substance (List 4A) meaning that as a pesticide, Guar Gum is considered by the EPA to pose little or no risk to humans or the environment. The Us Department of Agriculture (USDA) National Organic Program (NOP) also allows the use of Guar Gum in a variety of applications, but primarily as a pesticide in organic production operations. Finally, Guar Gum is listed on the Generally Recognized as Safe (GRAS) list by the Food and Drug Administration (FDA).

48-hr  $LC_{50} = >100\%$  for *Daphnia magna* when runoff generated using ASTM D7101 (2"/hr rainfall rate) was tested according to EPA-821-R-02-012.

DISPOSAL CONSIDERATIONS

Normally can be disposed of as a wood residue. Ensure disposal is in compliance with local, provincial (state), and federal regulations.

14 TRANSPORT INFORMATION

DOT Class: Not regulated #





Builders' Solutions Flexterra® High Performance-Flexible Growth Medium™(HP-FGM™)

MSDS Number: CON062

Revision Date: 1/1/14 Page 5 of 5

15

**REGULATORY INFORMATION** 

COMPONENT / (CAS/PERC) / CODES

\*Guar gum (9000300 n/a%) TSCA

**REGULATORY KEY DESCRIPTIONS** 

MASS = MA Massachusetts Hazardous Substances List NRC = Nationally Recognized Carcinogens OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance CSWHS = Clean Water Act Hazardous substances EHS302 = Extremely Hazardous Substance EPCRAWPC = EPCRA Water Priority Chemicals HAP = Hazardous Air Pollutants NJEHS = NJ Extraordinarily Hazardous Substances NJHS = NJ Right-to-Know Hazardous Substances OSHAPSM = OSHA Chemicals Requiring process safety management SARA313 = SARA 313 Title III Toxic Chemicals

**TSCA** = Toxic Substances Control Act

16	OTHER INFORMATION